

TAG – Laminate Tags

Laminate Manila Tags for on-site manual marking. Made from PP, with a self-laminating polyester top foil to protect the label marking. Technical labels or self-adhesive labelling tape from handheld printers can be applied.

Physical data

Top-Film:

Polyester (O-PET)

Thickness: 50µ

Halogen free

Color: Transparent

Adhesive:

Long life adhesive especially selected for lamination application.

UV resistant pressure sensitive acrylic adhesive.

High adhesion on low energy surfaces.

Acrylic based adhesive.

Liner:

One side siliconized, totally chlorine-free (TCF), wood-free Kraft paper.

Weight: 120 g/m²

Color: White

Carrier-Film:

UV stabilized Polypropylene (PP)

Thickness: 500 µ

Color: Yellow

Halogen free



Colors

Yellow

Operating temperature

-10°C to +60°C.

Application temperature

>+10°C.

Service Lifetime

DTI has tested the product according to DS 1094.4: Expected service lifetime for the product is minimum 10 to 15 years without delamination.

General remark

Long-term heat- and/or UV exposure may result in discoloration of the product.

Notes

This information and data is believed to be accurate and reliable. Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of this date, Link Solutions makes no representations as to the completeness or accuracy thereof. We place at your disposal the technical information necessary for the correct use of our products. As conditions and methods of use are beyond our control, that the person receiving the same will make their own determination as to the suitability for their purpose.

We reserve the right to modify characteristics with the aim of improving the product and adapting it to the requirements of the market